

Phone: 514-482-5984

Fax: 514-482-3685

sales@splicetronics.com

www.splicetronics.com



Splicetronics Solutions

Splice Tape is used to join component reels and reduce pick & place machine down-time

Advantages:

- Significant savings on production costs
- Increase pick & place machine output 5%-30%
- Reduce reel change down-time
- Guarantees a precise connection of reels
- Decrease machine abrasion by reducing the need to reload the feeder
- Used with the splicing tool and brass clip

BROWN SPLICE TAPE



Description:

- Sizes: 8mm, 12mm, 16mm, 24mm
- Strip Strength: $\geq 300\text{N/M}$
- Extending Rate: 55%
- Fire-retardant: 94v-0 class
- Insulating Grade: H
- Insulating Resistance: $>10^6$
- Peel Strength: 16N/25mm
- Tensile Strength: 110 N/25mm
- Resist Voltage: 7KV
- Total Thickness: 0.025mm

Instructions:

| | |
|---|--|
| | |
| Use the cutting tool to cut the tape at 90 degrees. | Using the pin guides, mount the brass clip onto the tool. Mount the two reels, center and clamp. |
| | |
| Remove a single strip of single splice tape. | Apply the strip to the top of the connecting reel. |

| P/N | Category | Qty/Unit |
|-------|--------------------------|----------|
| SS108 | Single Brown Splice 8mm | 1000 pcs |
| SS312 | Single Brown Splice 12mm | 1000 pcs |
| SS316 | Single Brown Splice 16mm | 1000 pcs |
| SS324 | Single Brown Splice 24mm | 1000 pcs |

Splicetronics Solutions will allow you increase manufacturing productivity and reduce operational costs