

Phone: 514-482-5984

Fax: 514-482-3685

sales@splicetronics.com

www.splicetronics.com



Splicetronics Solutions

Splice Tape is used to join SMT component reels and reduce pick & place machine downtime

Advantages:

- Strong adhesive bond
- Used with the splicing tool and clip
- Significant savings on production costs
- Increase pick & place machine output 5%-30%
- Reduce reel change downtime
- Guarantees a precise connection of reels
- Decrease machine abrasion by reducing the need to reload the feeder

BLUE SINGLE SPLICE TAPE



Description:

- Sizes: 8mm, 12mm, 16mm, 24mm
- Backing Thickness (um): 25
- Total Thickness (um): 55±2
- Peel Strength (N/25mm)
 - to steel (25mm*20min): 16
- Retention (H) (25mm*25min): >100
- Tensile strength at break (N/25mm): >80
- Elongation at break (%): >90

Instructions:

Use the cutting tool to cut the tape at 90 degrees.	Using the pin guides, mount the brass clip onto the tool. Mount the two reels, center and clamp.
Remove a single strip of single splice tape.	Apply the strip to the top of the connecting reel.

P/N	Category	Qty/Unit
SSB08	Blue Single Splice Tape 8mm	4000 pcs
SSB12	Blue Single Splice Tape 12mm	4000 pcs
SSB16	Blue Single Splice Tape 16mm	4000 pcs
SSB24	Blue Single Splice Tape 24mm	2000 pcs

Splicetronics Solutions will allow you to increase manufacturing productivity and reduce operational costs