

SPLICE TAPE & CLIP

Splicetronics Solutions

Part (reel)	Dimensions (pc)	Package
CS108 (8mm)	45mm x 4.8mm (tape)	500pcs/box
CS112 (12mm)	45mm x 7mm (tape)	500pcs/box
CS116 (16mm)	45mm x 9.5mm (tape)	500pcs/box
CS124 (24mm)	45mm x 17mm (tape)	250pcs/box



APPLICATION

- S Yellow strip of PET tape conveniently connected with a splice clip used to join SMT carrier tapes
- S Use with the splice tool (ST110/ST310)
- © 32mm-44mm and other colors available upon request

ADVANTAGES

- S Increase Pick and Place machine output by 5% - 30%
- S Reduce reel change downtime
- S Decrease machine abrasion by reducing the need to reload the feeder
- S Labor-saving innovative design

INSTRUCTIONS

- (S) Use the cutting tool (CT210/CT410) to accurately cut the carrier tapes.
- S Place the splice clip (teeth up) on the splice tool's placement pins.
- S Center both carrier tapes (cover tape up) on the pins, and secure with the clamps.
- © Crimp the tool handle to connect the carrier tapes.
- S Remove the release liner of the connected splice tape to reveal the adhesive side.
- § Fold over the tape strip onto the cover tape and press firmly.
- S Remove and discard the clear plastic cover to complete the splice.







