

SPLICE TAPE & CLIP

Splicetronics Solutions

Part (reel)	Dimensions (pc)	Package
CSP08 (8mm)	40mm x 2mm/4.5mm	500pcs/box
CSP12 (12mm)	40mm x 2mm/8mm	500pcs/box
CSP16 (16mm)	40mm x 2mm/12mm	500pcs/box
CSP24 (24mm)	40mm x 2mm/18.5mm	250pcs/box



APPLICATION

- S Black strips of PET tape conveniently connected with a splice clip used to join SMT carrier tapes
- S Use with the splice tool (ST110/ST310)
- § 32mm-44mm available upon request

ADVANTAGES

- S Necessary for Panasonic machines with an intelligent feeder
- S The black strip allows the sensor to detect the splice
- S Labor-saving innovative design

INSTRUCTIONS

- (S) Use the cutting tool (CT210/CT410) to accurately cut the carrier tapes.
- § Place a splice clip (teeth up) on the splice tool's placement pins.
- © Center both cut carrier tapes on the pins, and secure with the clamps.
- © Crimp the handle to connect the carrier tapes.
- S Remove the release liner of the splice tape to reveal the adhesive side.
- § Fold over the tape strip onto the cover tape and press firmly.
- (§) Remove and discard the clear plastic cover to complete the splice.







