

DOUBLE SPLICE TAPE

Splicetronics Solutions

Part (reel)	Dimensions (pc)	Package
DPL08 (8mm)	48mm x 3/3.5/4mm	500pcs/box
DPL12 (12mm)	48mm x 3/2/7/2mm	500pcs/box
DPL16 (16mm)	48mm x 3/2/11/2mm	500pcs/box
DPL24 (24mm)	48mm x 3/2/19/2mm	250pcs/box



APPLICATION

- Souble strips of black PET tape used to join SMT carrier tapes
- S Possible to use without the splice tool and clip
- § 32mm-44mm available upon request

ADVANTAGES

- S Necessary for Panasonic machines with an intelligent feeder
- S The black strip allows the sensor to detect the splice
- S Placement holes for easy alignment

INSTRUCTIONS

- (3) Use the cutting tool to accurately cut the carrier tapes.
- ③ Place the splice tape (face down/Arrow>) on the alignment jig.
- (3) Remove the release liner of the splice tape to reveal the adhesive side
- ③ Place the cut carrier tapes (cover tape down) on the splice tape strip.
- ③ Remove the joined carrier tapes from the alignment jig.
- § Fold over the strips to the underside of the carrier tape and press firmly.
- (§) Remove and discard the clear plastic cover to complete the splice.





