




DOUBLE SPLICE TAPE

Splicetronics Solutions

Part (reel)	Dimensions (pc)	Package
DSG08 (8mm)	40mm x 4.8mm	500pcs/box
DSG12 (12mm)	40mm x 7mm	500pcs/box
DSG16 (16mm)	40mm x 9.5mm	500pcs/box
DSG24 (24mm)	40mm x 17mm	500pcs/box



APPLICATION

- Ⓢ Double strips of transparent green PET tape used to join SMT carrier tapes
- Ⓢ Possible to use with or without the splice tool and clip
- Ⓢ 32mm-44mm available upon request

ADVANTAGES

- Ⓢ Increase Pick and Place machine output by 5% - 30%
- Ⓢ Reduce reel change downtime
- Ⓢ Decrease machine abrasion by reducing the need to reload the feeder
- Ⓢ Placement guide for easy alignment

INSTRUCTIONS

- Ⓢ Use the cutting tool (CT210/CT410) to accurately cut the carrier tapes.
- Ⓢ Remove the release liner of the splice tape to reveal the adhesive side.
- Ⓢ Align the cut carrier tapes (cover tape down) with the placement guide.
- Ⓢ Place both joining carrier tapes onto the first strip of the splice tape.
- Ⓢ Fold over the second strip to the underside of the carrier tape and press firmly.
- Ⓢ Remove and discard the clear plastic cover and guide to complete the splice.

