



DOUBLE SPLICE TAPE

Splicetronics Solutions

Part (reel)	Dimensions (pc)	Package
DSP08 (8mm)	40mm x 9.6mm/4.5mm	500pcs/box
DSP12 (12mm)	40mm x 6mm/4.3mm	500pcs/box
DSP16 (16mm)	40mm x 8mm/4.3mm	500pcs/box
DSP24 (24mm)	44mm x 17.4mm/4.7mm	250pcs/box



APPLICATION

- Ⓢ Double strips of black PET tape used to join SMT carrier tapes
- Ⓢ Possible to use with or without the splice tool and clip
- Ⓢ 32mm-44mm available upon request

ADVANTAGES

- Ⓢ Necessary for Panasonic machines with an intelligent feeder
- Ⓢ The black strip allows the sensor to detect the splice
- Ⓢ Placement guide for easy alignment

INSTRUCTIONS

- Ⓢ Use the cutting tool (CT210/CT410) to accurately cut the carrier tapes.
- Ⓢ Remove the release liner of the splice tape to reveal the adhesive side.
- Ⓢ Align the cut carrier tapes (cover tape down) along the splice tape guide.
- Ⓢ The carrier tape holes must be in line with the placement guide.
- Ⓢ Fold over the second strip to the underside of the carrier tape and press firmly.
- Ⓢ Remove the edge guide and fold the final strip over the carrier tape holes.
- Ⓢ Remove and discard the clear plastic cover to complete the splice.

