

Phone: 514-482-5984

Fax: 514-482-3685

sales@splicetronics.com

www.splicetronics.com



Splicetronics Solutions

ADVANTAGES:

- Individual strips of tape used with the splice tool and clip/shim.
- Guarantees a secure connection of SMT component reels.
- Increase SMT Pick and Place Machine output by 5% - 30%.

DESCRIPTION:

- Sizes: 8mm - 44mm
- Backing Thickness (um): 25
- Total Thickness (um): 53±2
- Peel Strength (N/25mm): ≥13
- Retention (H/25mm*25mm): >100
- Breaking Strength (KN/m): >4.0

P/N	Category (Actual Width)	Qty/Unit
SS108	Single Splice 8mm (5mm) *	1000 pcs
SS312	Single Splice 12mm (7mm)	1000 pcs
SS812	Single Splice 12mm (8mm)	1000 pcs
SS316	Single Splice 16mm (10mm)	1000 pcs
SS324	Single Splice 24mm (15mm)	1000 pcs
SS332	Single Splice 32mm (25mm)	1000 pcs
SS344	Single Splice 44mm (32mm)	1000 pcs

* Custom width available

SINGLE SPLICE TAPE



INSTRUCTIONS:

Cut the component reel at 90 degrees.	Using the pin guides, place the brass clip onto the tool. Add the two reels, center and clamp.
Remove a strip of single splice tape.	Apply the strip to the top of the connecting reel.