



# SINGLE SPLICE TAPE

Splicetronics Solutions

Part (reel)	Dimensions (pc)	Package
SS108 (8mm)	45mm x 5mm	1000pcs/box
SS312 (12mm)	45mm x 7mm	1000pcs/box
SS316 (16mm)	45mm x 10mm	1000pcs/box
SS324 (24mm)	45mm x 15mm	1000pcs/box



## APPLICATION

- Ⓢ Individual strips of yellow PET tape used to join SMT carrier tapes
- Ⓢ Use with the splice tool and clip to create a stronger connection, especially on larger carrier tapes
- Ⓢ Custom widths available upon request

## ADVANTAGES

- Ⓢ Increase Pick and Place machine output by 5% - 30%
- Ⓢ Reduce reel change downtime
- Ⓢ Decrease machine abrasion by reducing the need to reload the feeder

## INSTRUCTIONS

- Ⓢ Use the cutting tool (CT210/CT410) to accurately cut the carrier tapes.
- Ⓢ Place a splice clip (teeth up) on the splice tool's placement pins.
- Ⓢ Center both carrier tapes (cover tape up) on the pins, and secure with the clamps.
- Ⓢ Crimp the tool handle to connect the carrier tapes.
- Ⓢ Remove the release liner of the splice tape to reveal the adhesive side.
- Ⓢ Add a single strip to the cover tape and press firmly to complete the splice.

